

Buitenunit




AOYG07-12KPCA

Inclusief



infrarood
afstandsbediening

Optioneel



Wireless LAN
USB adapter



Type binnenunit		ASYG07KPCA	ASYG09KPCA	ASYG12KPCA
Type buitenunit		AOYG07KPCA	AOYG09KPCA	AOYG12KPCA
Energielabel		A++/A+	A++/A+	A++/A+
Nom. koelvermogen	kW	2,0(0,9~2,8)	2,5(0,9~3,0)	3,4(0,9~3,7)
Nom.verwarmingsvermogen	kW	2,5(0,9~3,4)	2,8(0,9~3,8)	3,8(0,9~4,8)
Verwarm. vermogen bij -10/ 20°C	kW	2,04	2,41	2,78
Ontvochtigingscapaciteit	l/h	1	1,3	1,8
SEER koelen	kW/kW	6,7	6,7	6,7
SCOP verwarmen	kW/kW	4	4	4,1
Luchthoeveelheid binnenunit	m³/h	580/460/340/240	580/460/340/240	630/490/360/240
Geluidsniveau binnenunit	dB(A)	45/38/31/22	45/38/31/22	46/40/33/22
Geluidsniveau buitenunit	dB(A)	45/46	47	49/51
Afm. binnenunit (hxbxd)	mm	270/784/224	270/784/224	270/784/224
Afm. buitenunit (hxbxd)	mm	541/663/290	541/663/290	541/663/290
Gewicht (netto) binnenunit	kg	8	8	8
Gewicht (netto) buitenunit	kg	23	23	25
Koelleiding diam. pers-zuig	inch	1/4-3/8 (A)	1/4-3/8 (A)	1/4-3/8 (A)
Min.-max. leidinglengte	m	5-20	5-20	5-20
Max. hoogteverschil	m	15	15	15
Vulling/ lengte/ per mtr	g/m/ g/m	550/15/20	550/15/20	590/15/20
Condensafvoer inw./uitw.	mm	11,8/15-16,8	11,8/15-16,8	11,8/15-16,8
Voeding	V/Hz	230/ 50	230/ 50	230/ 50
Elektro kabel binnen/buiten		3+1	3+1	3+1
Hoofdvoeding aansluiten		buiten	buiten	buiten
Opgenomen stroom	A	3,2	3,8	5,6
Opgenomen vermogen	kW	0,48/0,63	0,71/0,79	1,1/1,14
Advies afzekerverwaarde	A	16	16	16
Werkgebied koelen	°C	-10 ... +46	-10 ... +46	-10 ... +46
buitenunit verwarmen	°C	-15 ... +24	-15 ... +24	-15 ... +24